

NEUSPEED®

DSG BILLET ALUMINUM FILTER HOUSING

FITS: AUDI A3/S3(8P/8V), TT(8J), VW GOLF V/VI/VII, JETTA V/VI, EOS, PASSAT(B6/B7)
WITH DSG TRANSMISSION

DIRECT REPLACEMENT FOR OEM FILER HOUSING #02E 305 045
PART #95.10.60

INSTALLATION INSTRUCTIONS



PARTS LIST: 1 - BILLET FILTER HOUSING

TOOLS REQUIRED: 1 - 10MM SOCKET
1 - 13MM SOCKET
1 - 24MM SOCKET
1 - SMALL SCREWDRIVER

1. Removal of factory air filter box or aftermarket intake is required to access top of DSG transmission.
2. Using 10mm wrench or socket disconnect battery cables, ground cable first then positive cable.
3. Remove the 13mm hex bolt on battery hold down bracket, and then remove battery.
4. Remove the (3) 10mm hex bolts mounting the battery tray to vehicle. Unclip all wire cable support attachments from battery tray.
5. Using a 24mm socket unscrew the OE filter housing and remove. A little oil will drain out so use rags around base of housing.
6. Either install new filter and O-ring at this time or re-use the original filter and re-install O-ring onto *NEUSPEED* Filter Housing in groove at top of threads. Lightly coat with DSG oil.
7. Install *NEUSPEED* Filter Housing using 24mm socket and torque to 20Nm (15 ft/lbs).
8. Re-install battery tray, battery and intake in reverse of disassembly.
9. Turn ignition to ON position, wait 30 seconds then start engine and check for oil leaks.

©Copyright 2015, *NEUSPEED*®.
All rights reserved.
Reproduction in whole or in part prohibited.
DOC.95.10.60 Rev. 06.30.15